

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
5 August 2004 (05.08.2004)

PCT

(10) International Publication Number  
**WO 2004/066546 A1**

(51) International Patent Classification<sup>7</sup>: **H04L 1/00**

(21) International Application Number:  
**PCT/IB2004/000048**

(22) International Filing Date: 5 January 2004 (05.01.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
10/248,448 21 January 2003 (21.01.2003) US

(71) Applicant (for all designated States except US): SONY  
ERICSSON MOBILE COMMUNICATIONS AB  
[SE/SE]; Nya Vattentornet, S-221 88 Lund (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): JOHNSON, Phillip,

Marc [US/US]; 2830 Crestscene Trail, Raleigh, NC 27603  
(US). ASOKAN, Ramanathan [IN/US]; 303 Jaslie Drive,  
Cary, NC.27511 (US).


(74) Agent: STEPHENS, Gregory, A.; Moore & Van Allen  
PLLC, 2200 West Main Street, Suite 800, Durham, NC  
27705 (US).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: SPEED DATA RECEIVER WITH DETECTION OF CHANNEL CODING RATE



(57) Abstract: Disclosed is a system and method for channel decoding speech frames in a receiver capable of multiple (M) codec modes, wherein channel encoded speech frames include an inband bit portion and a speech portion. An inband bit decoder decodes the inband bit portion (700) of a received frame to obtain confidence levels associated with each of the M codec modes. Using these confidence levels, the codec modes are ordered from most to least likely. The speech frame is then decoded by a channel decoder using the most likely codec mode (704). A frame determination check (720) is performed to determine the quality of the decoded speech frame. If the decoded speech frame is determined to be of poor quality, then the channel decoding process is repeated using the next most likely codec mode (736) corresponding to the next highest inband bit decoding confidence level. This process is repeated until a good speech frame is decoded or some exit criteria is reached.

BEST AVAILABLE COPY

WO 2004/066546 A1